

DIGITUS Aluminum Outlet Strip, 6 safety outlets with circuit breaker

DN-95417
EAN 4016032456636



DIGITUS 1U Aluminum PDU, rackmountable 6x safety outlet, 16A, 4000W, 250VAC 50/60Hz,

Order and flexibility in the server rack with the DIGITUS® professional socket strips. Plug your devices centrally into the 45° arranged shockproof sockets. Therefore, blocked or obscured adjacent sockets are a thing of the past. The socket strips are perfectly suited for 482.6 mm (19") server racks and network cabinets and offer sophisticated features. With the supplied mounting brackets, the socket strip fits easily into the 482.6 mm (19") grid of your network cabinet and looks neatly arranged. Designed for horizontal mounting, with vertical mounting being possible as well. In addition, the mounting bracket can be fixed on the socket strip in 8 different positions, 45° and 90° in 4 directions. The supply lines to the socket strip are protected by the integrated circuit breaker, which prevents overloading of the feed cabling.

Safety, order and flexibility in the server rack - the DIGITUS® 482.6 mm (19") socket strips.

- 6 child safety outlets 250VAC 50/60Hz / 16A / 4000W
- Circuit Breaker: 16 A, Type-C
- Circuit breaker: Short-circuit breaking capacity (I_{cn} & I_{cs}) - 6000A
- 45° arranged sockets: No blocking or obscuring of adjacent sockets
- Mounting bracket for 482.6 mm (19") mounting

- Mounting brackets are variably fixed in 8 positions, 90° and 45° in 4 directions
- High quality aluminum casing
- Child safety device: Plastic covers close the contacts on the socket
- Input voltage: 230 V/AC
- Frequency: 50 ~ 60 Hz
- Mains supply line with earthing contact plug: 1.8 m, 3G x 1.5 mm²
- Measurements: L 48,1 x B 4,5 x H 8,3 cm
- Weight: 800 g
- Color: silver/black
- Additional Features: Circuit breaker
- Current: 16 A
- Input Plug: CEE7/7
- Installation: Desktop, Rack 0U, Rack 1U
- Outlets: CEE 7/3
- Phase: 1ph
- Power: 3,6 kVA
- Volts: 230 V
- Inch form factor (IEC 60297): 482.6 mm (19")

Package contents

- 1 x 482.6 mm (19") Aluminum 6-Outlet Socket Strip, 1 U with Circuit Breaker
- 2 x 482.6 mm (19") variable mounting brackets
- 1x user manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	10	8.00	48.00	37.00	32.00	56,832.00
Packaging Unit Inside	1	0.80	12.00	65.00	5.80	4,524.00
Packaging Unit Single	1	0.80	78.00	12.00	8.50	7,956.00
Net single without Packaging	1	0.71	78.00	12.00	8.50	7,956.00

More images:

