

DIGITUS 4 port gigabit network switch, industrial, unmanaged, 1 RJ45 uplink

DN-651118
EAN 4016032458838



Industrial 5-Port Gigabit Switch DIN rail, extended temp. range

The DIGITUS® Industrial Gigabit Switch is designed for harsh environments where it is exposed to humidity, temperature fluctuations and vibrations. With a temperature range of -40°C to 80°C, the Industrial Gigabit Switch can be used under the most adverse conditions. Constant availability is guaranteed in highly sensitive areas such as transportation, production, traffic and security surveillance. Thanks to the simple plug-and-play system, the Industrial Gigabit Switch can be quickly integrated into the respective environment. Gigabit connectivity makes the Industrial Gigabit Switch a flexible, cost-effective solution for industrial environments.

Robust and durable industrial solutions with standard and top-hat rail mounting

- 5 x 10/100/1000Base-TX Ethernet ports
- Automatic cable detection - Auto MDI / MDI-X function
- Supported standards: IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE802.3ab 1000BaseTX
- IEEE802.3x Flow Control and Back Pressure
- Store-and-forward technology for optimized data transfer
- Automatic speed and half/full duplex detection/adjustment
- Backplane with 14Gbps
- MAC address memory 2K
- Compact, robust metal housing

- Excellent protection against short circuits
- Lightning protection and surge protection
- Suitable for mounting on DIN rail (top-hat rail)
- Redundant power supply: 12~48 V DC, redundant power supply with polarity reversal protection function
- Extended operating temperature range, -40 °C ~ +80 °C
- Removable terminal connection
- Protection class: IP40
- Number of ports: 4
- Ethernet speed: Gigabit
- Industrial usage: yes
- Installation type: DIN rail
- Managed: no
- Number of ports (Uplink): 1
- Outdoorsuitable: no
- PoE (Power over Ethernet): no
- Protection against vandalism: no
- Uplink port connection: RJ45
- VLAN: no

Package contents

- Industrial 5-port Fast Ethernet switch
- Quick start guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	72	34.80	46.00	64.50	36.00	106,812.00
Packaging Unit Inside	1	0.48	13.50	16.20	5.30	1,159.11
Packaging Unit Single	1	0.48	13.50	16.20	5.30	1,159.11
Net single without Packaging	1	0.40	13.50	16.20	5.30	1,159.11

