


DIGITUS Cat. 7A class FA, S/FTP, Twisted Pair installation cable, 1000 m, simplex, 1500 MHz

DK-1744-A-VH-10-P
EAN 4016032462972



CAT 7A S-FTP installation cable, 1500 MHz Cca, AWG 22/1, 1000 m, SX, yellow

The DIGITUS® Cat. 7A S/FTP installation cable features the following cable structure 4x2x AWG22/1 and achieves a transmission frequency of up to 1500 MHz. The halogen-free cable sheath complies with the standards IEC 60332-3-24, FRNC-C, LSZH-3 and BauPVO Euroclass Cca. The cable is suitable for structured building cabling in secondary and tertiary areas. Complies with the standards ISO/IEC 11801, DIN EN 50173, DIN EN 50288-9-1.



Future-oriented standards and high-end quality for your network.

- Physical properties
- Cable: Bare copper wire, AWG 22/1
- System/s of AVCP: AVCP 3
- Insulation: SFS-PE (foamed polyethylene sheath)
- Total number of insulated conductors: 8, twisted in 4 pairs
- Color code: Blue-white, orange-white, green-white, brown-white
- Shielding of the individual pairs: Aluminum-covered polyester film, 100% coverage
- Overall shielding: Copper mesh
- Outer sheath: Dca to CCA complies with EN 50575
- Outer sheath thickness (nominal): 0.60 mm (CCA)
- Outer sheath color: Sulfur yellow (RAL 1028)
- Mechanical properties
- Cable grip: 150 N max.
- Dynamic bending radius: 8x AD mm min.
- Static bending radius: 4x AD mm min.

- Transport and storage temperature range: -20 °C to +75 °C
- Operating temperature range: -20 °C to +60 °C
- Installation temperature range: 0 °C to +50 °C
- External diameter simplex (nominal): 8.0 mm (CCA)
- Weight (kg/km): 68.0 kg (CCA)
- Electrical properties
- Impedance: 100 ± 5 ohm @ 1-1000 MHz
- Capacity: 40 pF/m nominal @ 1 KHz
- Capacity unbalance (pair earth): 1.6 pF/m max. @ 1 KHz
- Insulation resistance: 5 Gohm x km min.
- DC resistance: 72 ohm/km max. (2% max. non-balanced resistance)
- Loop resistance: 147 ohm/km max. (2% max. non-balanced resistance)
- Operating voltage: 72 VDC max.
- Insertion loss: 80 dB
- Phase delay: 450 nS/100 m max.
- Signal delay: 10 nS/100 m max.
- Segregation classification: "d" in accordance with EN 50174-2
- NVP: 75%
- Assortment: Twisted Pair Installation Cables
- Category: CAT 7A
- Shielding: S-FTP, pairs in metal foil and braid shielding
- CPR: Cca
- Length: 1000 m
- Color: yellow
- Jacket: LSOH
- Structure: 4 x 2 AWG 22/1, solid twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	66.50	53.00	53.00	43.50	122,192.00
Packaging Unit Inside	1	66.50	53.00	53.00	43.50	122,192.00
Packaging Unit Single	1	66.50	53.00	53.00	43.50	122,192.00
Net single without Packaging	1	66.09	53.00	53.00	43.50	122,192.00

More images:



CAT 7_A S/FTP
Twisted Pair Installation Cable,
1000 m, Simplex, C_{ca}

AWG 22/1 | 1500 MHz | CAT 7 | 20°/40° | LSZH | C_{ca} | CPE class

DK-1744-A-VH-SOP // CAT 7_A S/FTP Twisted Pair Installation Cable, 1000 m, Simplex, C_{ca}

Anwendungsbeispiel
Example of use

DK-1744-A-VH-SOP // CAT 7_A S/FTP Twisted Pair Installation Cable, 1000 m, Simplex, C_{ca}

Kabelquerschnitt
Cable cross section

Produktinformationen Product Information

Hersteller / Manufacturer	Digitus	Produkt / Product	DK-1744-A-VH-SOP
Artikelnummer / Article number	DK-1744-A-VH-SOP	Material / Material	1000 m, Simplex, C _{ca}
Artikelname / Article name	DK-1744-A-VH-SOP	Material / Material	1000 m, Simplex, C _{ca}

Technische Eigenschaften Technical Properties

Standard / Standard	ISO/IEC 11801 Class E	Standard / Standard	ISO/IEC 11801 Class E
Leistungsfähigkeit / Performance	1500 MHz	Leistungsfähigkeit / Performance	1500 MHz
Temperaturbereich / Temperature range	0°C - 60°C	Temperaturbereich / Temperature range	0°C - 60°C

Mechanische Eigenschaften Mechanical Properties

Material / Material	LSZH	Material / Material	LSZH
Lebensdauer / Lifetime	10 Jahre	Lebensdauer / Lifetime	10 Jahre

Leistungseigenschaften Transmission Properties

Strecke / Distance	AT	MT	PT	AT	MT	PT	AT	MT	PT
1	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
10	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
100	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
1000	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0


PREMIUM Zertifikat
No. 15874g-25

Hersteller / Manufacturer: Digitus

Produkt / Product: DK-1744-A-VH-SOP

Kategorie / Category: 7_A

Spezifisches Kabel, Kupfer, Kategorie 7_A
GHMT PREMIUM Verification Program, GHMT PVP



Digitus

Digitus ist ein führender Hersteller von Netzwerkprodukten.

Digitus ist ein führender Hersteller von Netzwerkprodukten.

Digitus ist ein führender Hersteller von Netzwerkprodukten.

