

DIGITUS FTTX enclosure with 4 x SC SX couplers

DN-931094
EAN 4016032466536



FTTX Outlet, with 4x SC (APC) SX adapter surface and DIN-rail mount

The FTTX housing can hold up to 4 fiber optic cables and distribute them to 4 end devices with the matching couplings. This housing is equipped with 4 x SC Simplex couplings; alternatively, 4 x LC Duplex couplings (without flange) can be inserted. The housing consists of a front panel, the housing with expandable splice cassette and a transparent plastic cover for additional protection of the spliced fiber optic cable. The box can be mounted on the wall or snapped onto a profile rail (DIN rail). Bring together fiber splices, terminations, storage and connections in a minimal space with the ultra-compact DIGITUS® FTTX.

FTTX housing for fiber splices, terminations, storage and connections in a compact protective housing

- Suitable for 4 ports: 4 x SC SX (integrated) / alternative: 4 x LC DX (not incl.) (without flange)
- Integrated splice cassette
- Protection type: IP45
- Installation: Wall or profile rail (DIN rail)
- Suitable for single-mode and multi-mode fiber optic cables
- Return loss: >50dB(UPC), 60dB(APC)
- Operating temperature: -40°C ~ +85°C
- Housing material: PC + ABS
- Dimensions: 100 x 80 x 30 mm (LxWxH)
- Weight: 0.4 kg (without couplings)

Package contents

- FTTX housing equipped with 4 x SC SX couplings

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	100	10.50	49.00	23.50	41.00	47,211.50
Packaging Unit Inside	1	0.11	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.11	9.30	10.50	3.80	371.07
Net single without Packaging	1	0.09	9.30	10.50	3.80	371.07

More images:



