

DIGITUS Smart Monitor Mount with integrated Docking Station, Gas Pressure Spring and Clamp Mount

DA-90405 EAN 4016032474586





Monitor Gas Spring Mount with USB-C Dock (5 Port) 30", 9kg max.,

The intelligent monitor arm solution with integrated docking station unites ergonomic design and comfort in an unprecedented manner. Users benefit from a perfectly ergonomically adapted monitor position and can also use their mobile devices such as notebooks, smartphones or tablets via a fixed monitor. The monitor arm supports displays with a screen diagonal from 15" to 30" (VESA 75 / 100) up to a maximum load of 9 kg. The integrated gas spring and quick-release function make it easier for you to position and clip in the monitor. You can access the interfaces of the integrated docking station centrally at the clamp mount. Use the HDMI, VGA and USB interfaces to connect your mobile device and also charge it via USB-C™ thanks to Power Delivery. Enjoy a tidy desk with the full connectivity of a docking station and the ergonomic advantages of the adjustable monitor bracket from DIGITUS®.

Monitor bracket and docking station in one – ergonomic design combined with practical mobile device connection

- Monitor bracket
- Suitable for monitors with dimensions between 15" and 30"
- · Maximum load capacity: 2 9 kg
- Quick release function: Simple clipping in of the monitor to the mount
- Swivel the mount by up to 360° (3 hinges)
- Inclination of the VESA bracket: -85° to +15°
- Supported VESA dimensions: 75x75, 100x100
- Maximum height adjustment: 47.7 cm
- For tabletop thicknesses between: 25 30 mm
- Material: Steel, aluminum, plastic
- Dimensions: W 67.3 x D 55.4 x H 14.3 cm
- Weight: 3.2 kg

- Color: Black
- · Docking station:
- 1 x HDMI port
- 1 x VGA port
- 1 x USB-C[™] host
- 1 x USB-C[™] with Power Delivery (PD 3.0 / 87 W max.)
- 2 x USB A USB 3.0 / SuperSpeed 5 Gbps max. / 5 V / 0.9 A
- · HDMI version: 1.4
- HDMI resolution: 4K 1 monitor / 1080p 2 monitors
- VGA resolution: Full HD (1080p)
- USB-C™ version: USB 3.1 Gen 1
- · Manufacturer's notice:
- Not all USB-C™ ports support all the features of the USB Type-C™ standard. Make sure that your notebook's USB-C™ port supports the DisplayPort Alternate Mode (DP Alt Mode) as well as USB Power Delivery (PD).
- An optional power adapter is required in order to use the charging function via Power Delivery.
- Simultaneous use of HDMI + VGA = Clone desktop
- Individual use of HDMI or VGA = Extend / Clone desktop

Attributes

- Monitor weight (max.): 9 kg
- Mounting method: Clamp-mount
- · Number of monitors: 1
- · Size of monitors: up to 32"
- VESA mount: 75x75 mm, 100x100 mm

Package contents

- 1 x Smart Monitor Bracket with Integrated Docking Station, Gas Spring and Clamp Mount
- 1 x Mounting material
- 1 x QIG

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	5	21.53	45.10	56.20	34.50	87,444.40
Packaging Unit Inside	1	4.31	0.00	0.00	0.00	0.00
Packaging Unit Single	1	4.31	31.80	42.80	10.90	14,835.30
Net single without Packaging	1	3.91	31.80	42.80	10.90	14,835.30



More images:























Safety notes

- Please read the entire manual before starting assembly and installation. Please contact your local dealer if you have any questions about the instructions or warnings.
- · CAUTION: Use with products that exceed the permitted weight may result in damage or possible injury.
- Brackets should be fitted in accordance with the installation instructions. Incorrect installation can result in damage or injury.
- Use safety equipment and suitable tools. The product should only be installed by specialists.
- This product can be installed on timber-framed, solid concrete or stone walls.
- The load-bearing surfaces should be able to safely withstand the entire weight of appliances and all additional components.
- Only use the installation screws supplied and DO NOT TIGHTEN the screws TOO TIGHT.
- · This product contains small parts that can cause a choking hazard if swallowed. Keep these parts away from children.
- Only use this product indoors. Using the product outdoors can lead to injuries and damage.
- IMPORTANT: Before installation, please compare all components received with the components list. If parts are damaged or missing, ask your local dealer for replacement parts.
- MAINTENANCE: Check the bracket regularly for safety and stability (preferably every three months).

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com



info@assmann.com