

DIGITUS KVM Switch, 2 Port, 4K30Hz, USB-C/USB/HDMI in, HDMI out, Network

DS-12901
EAN 4016032479987



2port Type C KVM with Network Port

The DIGITUS® 2-port KVM switch with USB-C™ and network connectivity gives you the ability to control two 4K-capable PCs from a single USB keyboard and mouse. Conveniently switch between the two PCs at the touch of a button, eliminating the need to reconnect all cables. The Gigabit network port provides convenient access to the network via the additional USB-C™ port. The output to a monitor is done via the integrated HDMI output. Audio signals from the microphone and speakers can also be switched. In addition, another USB-C™ port and two USB A (2.0) ports are available on the front, which can be used for further peripherals such as USB sticks or external hard drives. Status LEDs on the front of the switch show you the current status at all times. The slim switch is rounded off by the robust metal housing.

New generation KVM switch support USB-C™ notebook computer It provides USB console, HDMI display, Hub, network and power to USB-C™ notebook computer via 1 USB-C™ cable .

- Inputs: 1 x HDMI computer, 1x USB-C™ computer, 1 x Gigabit network (RJ45), 2 x USB A (keyboard, mouse), 1x USB-C™ power (optional)
- Output: 1 x HDMI video
- Additional connections on the front: 2 x USB A 2.0, 1 x audio input, 1 x audio output , 1 x USB-C™ (for USB-C™ computer only)
- Provide LAN connection to USB-C™ notebook computer via USB-C™ cable

- Audio in/out: 3.5 mm audio jacks
- LED status indicator on front: 2 x, shows active computer
- Switch: Switching PC1 / PC2
- Switching time: 0.2s
- HDMI® version: 1.4
- HDCP version: 1.4/2.2
- UHD resolution: 3840 x 2160p / 30 Hz
- Subsampling: YCbCr 4:4:4/ YCbCr 4:2:2/ YCbCr 4:2:0
- Bandwidth HDMI: 10.2 Gbps all channels (3.4 Gbps per channel)
- Color depth HDMI®: 24/36 bit (all channels).
- Power supply via USB-C™port on the rear panel (Optional)
- USB-C Power delivery : 20 V / 5 A / 100 W max.
- Operating temperature: 0°C ~ 50°C
- Storage temperature: -20°C ~ 60°C
- Operating humidity: 0% - 80% RH (non-condensing)
- housing material: metal
- dimensions: 150 x 88 x 26 mm (WxDxH)
- Weight: 400 g
- Color: Black

Package contents

- 1 x KVM-Switch, 2-Port, HDMI , USB-C
- 1 x QIG
- 1 x KVM Cables 1.2m
- 1 x USB-C calbe 0.5m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	0.80	21.00	49.50	53.50	55,613.20
Packaging Unit Inside	1	0.04	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.04	13.00	19.80	9.80	2,522.52
Net single without Packaging	1	-0.09	13.00	19.80	9.80	2,522.52

More images:

