

DIGITUS 4K HDMI - AOC - Armored Connecting Cable with Protective Sleeve

AK-330130-300-S
EAN 4016032483809



HDMI AOC Connection Cable, Type A, armored M/M, 30.0m, for Plugs IP68, UHD, 4K@60 Hz, gold,bl

This active HDMI® AOC Hybrid Fiber Optic Cable is ideally suited for transferring uncompressed video and audio data with high bandwidth over longer distances. The hybrid construction, which uses copper and fiber optic cable, prevents electromagnetic interference. This ensures a loss-free transfer along the entire length of the cable with UHD resolution of up to 4K/60Hz and bandwidths of up to 14.4 Gbps. The use of fiber optic cable keeps the diameter of this active cable very low (OD: 5.2 mm). The steel and aramid fiber construction of the cable ensures optimal protection against external forces, making the cable crush-proof and puncture-resistant. When the cable is not in use, the protective sleeves protect the connections (IP68). The ideal companion for use at trade fairs, concerts and other events. The simple Plug and Play installation is user-friendly; just plug it in and immediately enjoy optimal image quality. It supports numerous standards such as HDMI 2.0, HDCP 2.2 and HDR. Some of the many audio features supported are ARC, DTS-HD Master Audio and Dolby TrueHD. Cutting edge chip technology makes it possible to transfer the full HDMI® signal spectrum while also supporting uncompressed CED and EDID with very low latency.

- Supports up to 4K with 50/60Hz
- Supports up to 4K 3D
- Signal transmission rate up to 14.4 Gbps
- Supports up to 120Hz at Full HD
- Supports 1080p 3D HFR
- HDCP 2.2, HDCP 1.4
- HDMI 2.0 (downward compatible)

- Supports HDR10 (High Dynamic Range)
- Supports Audio Return Channel (ARC)
- Supports Consumer Electronic Control (CEC)
- Supports lip-sync (audio/video synchronization)
- Multi stream audio/video support
- Latency: Zero frame delay
- Cable sheath: LSZH halogen-free
- Bending radius: 25.4 mm
- Operating temperature: -45 ~ 85°C
- Operating humidity: < 90% RH
- Power consumption: 250 mW max.
- Supports DVI version 1.0
- Permissible tensile strength: 1000N
- Waterproof closure: IP68
- Pull-off force of the plug: MIN 10N
- Insertion force of the plug: MAX 35N
- Flame protection class: UL94V-0
- Color cable: black
- Connector 1: HDMI type A, plug
- Connector 2: HDMI type A, plug
- Connector surface: gold-plated
- Ferrite filter: none
- HDMI Standard: Premium High Speed HDMI with Ethernet
- HDTV Resolution max.: 4096 x 2560 Pixel, 60Hz
- HDTV Standard: Ultra HD 4K
- Hoods: Metallic housing
- Length: 30 m
- AOC - Active Optical Cable: yes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	16.30	23.00	44.00	36.00	36,432.00
Packaging Unit Inside	1	1.63	0.00	0.00	0.00	0.00
Packaging Unit Single	1	1.63	20.50	21.70	6.80	3,024.98
Net single without Packaging	1	1.02	20.50	21.70	6.80	3,024.98

More images:

