

DIGITUS USB 4.0 Type-C connection cable

DB-300443-030-S
EAN 4016032485889



USB 4 connection cable, TypeC to TypeC, Al-Housing PP Braid 8K@30Hz, PD3.0, 20Gbits/s, 3m, bl.

The Digitus® 3rd generation USB 4.0 cable with aluminum housing is the all-rounder among cables. Thanks to the Thunderbolt 3 protocol, PCI Express, DisplayPort and host-to-host transmissions can be realized. You can use this cable to transfer audio/video signals, data and power. The data transfer speed is 20 Gbit/s, which is 4x faster than USB 3.0 (5 Gbit/s) and 2x faster than USB 3.1 (10 Gbit/s). This allows you to transfer large data such as movies and music within seconds. The video signals are transmitted in max. 8K at a refresh rate of 30 Hz. In addition, the resolutions 5K (5120 x 2880) at 60 Hz. and 8K (7680 x 4320) @30Hz. (dual mode possible) are also supported. Thanks to USB Power Delivery Revision 3.0, the fast charging function is guaranteed. With the corresponding charger, you can charge your smart devices with max. 60 W (3 A / 20 V) in a short time. The USB Type-C interface enables broad compatibility with devices with this connection.

The USB 4.0 cable is an all-rounder and supports the following transmission types: audio/video/data transfer/charging function

- Supports: 8K (7680 x 4320) @30Hz.
- Supports: 5K (5120 x 2880) @60Hz.
- Supports data transfer rates of up to 20 Gbit/s
- Backwards compatible with Thunderbolt 3, USB 3.2, USB 3.1 and USB 2.0
- Supports USB Power Delivery Revision 3.0 (PD 3.0) with 20V, 3A and 60W
- Core material: CU
- Connection 1: USB type C, plug
- Connection 2: USB type C, plug
- Dimension plug 1 : 6.65*2.4mm
- Dimension plug 2 : 6.65*2.4mm
- Color connections: Black
- Contact surface: gold-plated

- Number of PINS: 22
- Hood: potted
- Cable outer material: PP
- Plug housing: Aluminum
- Cable outer diameter: 5.0 mm
- Tensile strength: 4 kg/min
- AWG: 30
- Bending radius: 60
- Cable color: Black
- Shielding: Double shielded
- USB-C product: yes
- Total weight: 45g
- Manufacturer's instructions:
- If you connect a USB-C monitor/TV/projector to a PC equipped with USB Type-C, please make sure that your USB-C display supports DisplayPort signal output.
- The video output capability depends on the graphics card of your notebook and the connected monitor. Some monitors also limit the available resolution.
- To use a dual 4K output, the USB 4 device must support the PD3.0 protocol

Attributes


- Color cable: black
- Connector 1: USB C, plug
- Connector 2: USB C, plug
- Connector surface: gold-plated
- Ferrite filter: none
- USB compliance: USB Type-C™
- Length: 3 m
- Shielding: Double shielding

Package contents

- 1x USB 4.0 Type-C connection cable

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	40	8.02	36.00	26.00	42.00	39,312.00
Packaging Unit Inside	20	4.01	17.00	24.00	41.00	16,728.00
Packaging Unit Single	1	0.20	8.00	23.00	4.00	736.00
Net single without Packaging	1	0.12	8.00	23.00	4.00	736.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com