

# DIGITUS CAT 6, modular couplers, shielded - 5 pieces

**AT-AG-8-8-C6S-5**  
**EAN 4016032495017**



**Modular Coupling, 8P8C, 1:1 shielded CAT6, metal housing, 5 pcs.**

The modular CAT 6 coupler from DIGITUS® consists of two shielded RJ45 sockets. The assignment is "1:1".

- Technical properties:
- Housing material: ABS UL-94V-0
- Contacts coating: Nickel, gold-plated 0.5 µ
- Shielding: Tinned bronze

- PCB:FR4, UL 94V-0
- Material contacts: Phosphor bronze
- Physical properties:
- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Insertion force: 30N max. (IEC 60603-7-5)
- Retention strength: 7.7 kg between jack and plug
- 5 pieces

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1000	11.67	30.00	55.00	27.00	44,550.00
Packaging Unit Inside	100	1.17	14.00	25.50	10.50	3,748.50
Packaging Unit Single	1	0.01	40.00	50.00	9.00	18,000.00
Net single without Packaging	1	0.00	40.00	50.00	9.00	18,000.00

**Safety notes**

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
 Auf dem Schüffel 3  
 Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)