

DIGITUS Hirose modular plugs TM31 for round cable, CAT 6A - 50 pieces

A-MO6A-8-8-HRS-50
EAN 4016032496250



Hirose Modular Plug, CAT6A TM31 8P8C, shielded, for round cable, incl. hood, 50 pcs.

These modular plugs can be used to establish quick and simple connections.

- Layout performance: CAT 6A, 10GBase-T
- Area of application: Patch cable assembly
- General properties:
- Fully shielded with strain relief for installation cables
- Incl. comb
- Technical properties:
- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Material connector body: Polycarbonat, clear
- Connector contact: Phosphor bronze, brass 0.8 μ gold-plated

- Material shielding housing: Brass 0.5 mm, 2 μ nickel-plated
- Flammability: UL 94V-2
- Physical properties:
- Insertion force: 30N max. (IEC 60603-7-5)
- Diameter Cu-Conductor: AWG (27/7 ... 24/7)
- Operating temperature: -20 °C to +60 °C
- Current carrying capacity: 1A at 50 °C
- Diameter outer jacket: 5,5 ... 6,2mm
- 50 pieces

Package contents

- 3 pieces: Plug, Cableholder, Grommet
- 50 pieces

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	50	3.50	105.00	110.00	50.00	577,500.00
Packaging Unit Inside	1	0.07	60.00	50.00	17.50	52,500.00
Packaging Unit Single	1	0.07	60.00	50.00	17.50	52,500.00
Net single without Packaging	1	-0.69	60.00	50.00	17.50	52,500.00

Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com