

# ednet Quick Charge™ 3.0 Car Charger, Dual Port

84103  
EAN 4054007841032



## Quick Charge 3.0 Car Charger, 2 Port Input 12-24V, Outputs: 3,6 - 6,5V/3A; 5V/2.4A

The ednet Quick Charge™ 3.0 Car Charger, Dual Port guarantees the fastest possible charging of your mobile devices. The Quick Charge™ 3.0 port supplies up to 3A output voltage and charges compatible smartphones and tablets to up to 80% in just 30-35 minutes. Using this, charge your mobile devices four times faster than conventional chargers. This is also backward-compatible with Quick Charge™ 2.0 and 1.0. Non-compatible devices can also be charged with up to 2.4A. Quickly charge all kinds of devices with up to 2.4A via the additional smart charging port. The two smart USB ports automatically detect the connected devices and individually deliver the required or best possible charging current. Through protection against overvoltage, overheating and short-circuit, the safety of your mobile devices, as well as of the adapter itself, is ensured.

### Thanks to Qualcomm® Quick Charge™ 3.0, charge your mobile devices four times faster than conventional chargers

- Qualcomm® Quick Charge™ 3.0 – Charges compatible smartphones and tablets four times faster than conventional chargers
- Qualcomm® Quick Charge™ 3.0 - Charges compatible smartphones and tablets to up to 80% in just 30-35 minutes
- Fast charging - Quick Charge™ 3.0 (3A max.) + smart charging (2.4A max.)

- Intelligent charging - both USB ports detect the connected devices and supply the individually required charging current
- Qualcomm® Quick Charge™ 3.0 - Charges 38% faster than Quick Charge™ 3.0
- Backward-compatible with Quick Charge™ 2.0 + 1.0
- Dual Port (Quick Charge™ 3.0 + smart charging) - Quickly and efficiently charge two mobile devices (such as smartphones, tablets, power banks, speakers, cameras, etc.) at the same time in your vehicle
- Output voltage Qualcomm® Quick Charge™ 3.0 Port: (3,6-6,5V/3 A; 6,5-9 V/2A; 9-12V/1,5A)
- Smart charging port output voltage: 5V/2.4A
- Input voltage: 12-24V
- Protection against overvoltage and short-circuit
- Protection against overcurrent and overheating
- LED activity indicator
- Qualcomm® certified
- Dimensions: L 6.9 x B 3 x H 3 cm
- Weight: 30 g
- Color: black

### Package contents

- Quick Charge™ 3.0 Car Charger, Dual Port
- QIG (quick installation guide)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	80	6.50	45.00	38.50	33.00	57,172.50
Packaging Unit Inside	1	0.08	13.70	10.00	3.50	479.50
Packaging Unit Single	1	0.08	13.70	10.00	3.50	479.50
Net single without Packaging	1	0.05	13.70	10.00	3.50	479.50

**More images:**



**Safety notes**

- Use charging adapters or power supply units in accordance with the instructions in the operating instructions to ensure optimum performance.
- Connect the charging adapter to an easily accessible socket in the voltage range between 100-240 V AC.
- Disconnect the charging adapter from the socket after use.
- Do not use the charging adapter with electronic devices that are outside the specifications of the charging adapter.
- Do not expose the device to rain, moisture, vapors or liquids.
- Do not insert any objects into the device.
- Do not attempt to repair the unit or open the housing without authorization. You risk an electric shock!
- Ensure adequate ventilation to prevent damage due to overheating.
- Dust, moisture, vapors and strong cleaning agents or solvents can cause damage to the device.
- Disconnect the appliance from the power supply and the connected devices before cleaning.
- Clean the device with a dust-free cloth.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)