

# DIGITUS Wall Mounting Cabinet Unique Series - double sectioned, pivoted

DN-19 07-U-3  
EAN 4016032186724



## 7U wall mounting cabinet, Unique, 420x600x600 mm double sectioned, pivotable, grey (RAL 7035)

The network cabinets for wall installation from the Unique series were developed for especially convenient and flexible network cabling. Thanks to the integrated hinge in the back frame, the housing can be folded to the side if needed, for example in order to easily carry out assembly work in the back area of the cabinet. There is a sliding cable inlet with foam rubber seal in the roof of each cabinet. The back wall and floor plate are equipped with pre-cut cable inlets with a plastic cover. In addition, the back frame is equipped with brush management panels on the top and bottom. To accommodate a fan module, the roof structure is also equipped with a pre-cut area. One pair of galvanized 483 mm (19") profile rails labeled with rack units readable in both directions are installed on the inside. Their depth can be adjusted. The back frame also has a 483 mm (19") perforation. Each cabinet is made of up to 1.5 mm thick sheet steel. Coloring is done with electrostatic powder coating in the standard colors gray (RAL 7035) or jet black (RAL 9005). Removable and lockable side walls in a modular design as well as lockable and removable front door improve accessibility. The door hinges can be switched. Wall installation is accomplished in two easy work steps: The housing frame plate is bolted on the wall to open in either direction and then connected with the housing. With optionally available levelling feet or casters, the wall housings from the Unique series can also be used as a free-standing unit.

**A série DIGITUS® Unique foi fabricada, concebida e desenvolvida para corresponder aos mais elevados requisitos da infraestrutura de TI.**

- Classe de proteção IP20

- Dispositivo de bloqueio de 1 ponto na porta frontal
- Os painéis laterais são bloqueáveis e amovíveis
- Calhas de perfil de 483 mm (19") montadas no lado frontal, dentro do armário, galvanizadas
- As calhas de perfil de 483 mm (19") podem ser ajustadas em profundidade e estão providas com marcação da unidade de altura
- Folha de aço robusta 1,1 - 1,5 com elevada capacidade de carga, pintada por pulverização
- O telhado está preparado para elemento de ventilação (entradas perfuradas)
- Ranhuras de ventilação para ventilação e saída ativa e passiva
- Vários pontos de ligação terra no armário, para componentes embutidos
- É fornecido completamente montado
- Cabinet type: Wall mounting cabinet
- Color: light grey, RAL 7035
- Depth: 600 mm
- Front door: Glass door, single opening
- Load capacity: 80 kg
- Side panels: Both sides
- Units: 7
- Width: 600 mm
- IP protection class: IP20
- Mounted: yes

### Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- 2 x Keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	1	32.50	65.00	65.00	47.00	198,575.00
Packaging Unit Inside	1	32.50	65.00	65.00	47.00	198,575.00
Packaging Unit Single	1	32.50	65.00	65.00	47.00	198,575.00
Net single without Packaging	1	31.50	60.00	60.00	42.00	184,275.00

**More images:**

