

DIGITUS Fiber optic patch cable, MPO, socket, OS2, method A, 1m

DK-2966-01
 EAN 4016032345121



Fiber Optic Patchcord, MPO to MPO, Female, OS2, SM 09/125 μ, 1m, APC, Method A, yellow/green

The MPO patch cable enables data rates of 40Gb/s or 100Gb/s and is the answer to the growing bandwidths required by data centers. The standardized IEC61754-7 and TIA/EIA 604-5 MPO connector guarantees the best performance in the entire network and is hardly larger than a standard RJ45 connector. The excellent attenuation and compact design make this patch cable the first choice when it comes to bandwidth and performance.

High-performance solutions for efficient and scalable connectivity in data centers.

- Plug: MPO socket
- Ground joint: APC
- Type: Method A
- Fiber type: SM-G652D, 9/125μ, OS2
- Number of fibers: 12
- Cable outer diameter: 3 mm
- Coat color: Yellow

- Cable length: 1 m
- Material of the outer sheath: LSZH
- Max. Tensile strength: 300 N
- Min. bending radius: 30 mm
- Temperature range: -40°C to +75°C
- Cable diameter: 3 mm
- Cable jacket: LSOH
- Color cable: yellow
- Fiber class: OS2
- Fiber diameter: 9/125μ
- Mode: Singlemode
- Number of connectors side 1: 1
- Number of connectors side 2: 1
- Number of fibers: 12
- Packaging: DIGITUS Polybag
- Length: 1 m

Package contents

- 1 x fiber optic patch cable, MPO, socket, OS2, method A, 1m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	400	5.47	40.00	40.00	30.00	48,000.00
Packaging Unit Inside	1	0.01	1.00	20.00	29.00	580.00
Packaging Unit Single	1	0.01	1.00	20.00	29.00	580.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00