

DIGITUS 1.25 Gbps copper SFP-module, RJ45

DN-81005
EAN 4016032389484



1.25 Gbps Copper SFP Module, RJ45 10/100/1000Base-T, up to 100m

The DIGITUS® Mini GBIC (SFP) transceiver modules offer the highest quality and reliability. The module offers a perfect opportunity for you to extend your Gigabit network switch with a free SFP Uplink Port around an additional RJ45 connection. Thanks to the hot-plug capability, you can install the module without any interruption to the network traffic or restart of the device. In addition, conformity with the MSA (Multi Source Agreement) standard provides compatibility with the current network switch manufacturers.

The plug and play extension for your network switch

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Up to 1.25 Gbps bidirectional maximum data rate

- Compliant to IEEE 802.3z Gigabit Standard
- High quality and excellent reliability
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant
- Hot pluggable - installation possible while in operation
- Auto MDI/MDI-X
- Connection: 1x RJ45, CAT 5
- Distance: up to 100 m
- Operating temperature: 0 °C ~ 70 °C
- Mode: Copper
- Connector: RJ45
- Distance (km): 0.1
- DDM Support: no
- Manufacturer compatibility: Universal (MSA)
- Ethernet speed: Gigabit

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	120	7.00	25.40	39.40	55.00	55,041.80
Packaging Unit Inside	30	1.75	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.06	3.20	9.30	12.00	357.12
Net single without Packaging	1	0.02	1.50	1.50	7.00	0.00

More images:



SFP Modules							
Product Number	MM Code	Speed	Distance	Connector	Mounting	Operating Temperature	Industrial Version
Fast Ethernet							
DM-8101	42780000400	100 Mbps	2 km	LC Multimode Duplex	191mm	0 to +70 °C	✓
DM-8102	42780000700	100 Mbps	550 m	LC Singlemode Duplex	191mm	0 to +70 °C	✓
DM-8104	42780000700	100 Mbps	550 m	LC Singlemode Duplex	191mm	0 to +70 °C	✓
10Gbps							
DM-8105	42780000800	10 Gbps	550 m	LC Multimode Duplex	191mm	0 to +70 °C	✓
DM-8106	42780000900	10 Gbps	200 m	LC Singlemode Duplex	191mm	0 to +70 °C	✓
DM-8107	42780001000	10 Gbps	200 m	LC Singlemode Duplex	191mm	0 to +70 °C	✓
DM-8108	42780001100	10 Gbps	200 m	LC Singlemode Duplex	191mm	0 to +70 °C	✓
DM-8109	42780001200	10 Gbps	200 m	LC Singlemode Duplex	191mm	0 to +70 °C	✓
10Gbps PoE							
DM-8110	42780001300	10 Gbps	200 m	LC Singlemode Duplex	191mm	-40 to +85 °C	✓
DM-8111	42780001400	10 Gbps	200 m	LC Singlemode Duplex	191mm	-40 to +85 °C	✓
DM-8112	42780001500	10 Gbps	200 m	LC Singlemode Duplex	191mm	-40 to +85 °C	✓
DM-8113	42780001600	10 Gbps	200 m	LC Singlemode Duplex	191mm	-40 to +85 °C	✓
DM-8114	42780001700	10 Gbps	200 m	LC Singlemode Duplex	191mm	-40 to +85 °C	✓
DM-8115	42780001800	10 Gbps	200 m	LC Singlemode Duplex	191mm	-40 to +85 °C	✓
DM-8116	42780001900	10 Gbps	200 m	LC Singlemode Duplex	191mm	-40 to +85 °C	✓
DM-8117	42780002000	10 Gbps	200 m	LC Singlemode Duplex	191mm	-40 to +85 °C	✓
DM-8118	42780002100	10 Gbps	200 m	LC Singlemode Duplex	191mm	-40 to +85 °C	✓
DM-8119	42780002200	10 Gbps	200 m	LC Singlemode Duplex	191mm	-40 to +85 °C	✓