

DIGITUS 4 port Gigabit Ethernet network PoE switch, industrial, unmanaged, 2 SFP uplink

DN-651109
EAN 4016032457923



Industrial Gigabit Ethernet PoE+ Switch 4-port PoE + 2-port SFP, 802.3at, DIN rail

The DIGITUS® Industrial Gigabit PoE switch is designed for harsh environments where they are exposed to humidity, temperature fluctuations and vibrations. With a temperature range of -40°C to 75°C, the Industrial Gigabit PoE switch can be used under the most adverse conditions. Thanks to the PoE ports with IEEE802.3af/at support, PoE-capable devices can be supplied with up to 30 W per port. Constant availability is guaranteed in highly sensitive areas such as transportation, production, traffic and security surveillance. The simple plug-and-play system allows the Industrial Gigabit PoE switch to be quickly integrated into the respective environment. Thanks to the Gigabit connectivity and the SFP uplink ports, the Industrial Gigabit PoE switch is a flexible, cost-effective solution for the industrial environment.

Robust and durable industrial solutions with integrated Power over Ethernet (PoE) function

- 4 x 10/100/1000Base-TX Ethernet PoE ports
- Supports IEEE802.3af/at
- Automatic cable detection - Auto MDI / MDI-X function
- Supported standards: IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.3z Gigabit Ethernet
- Backplane 12G

- MAC address memory 1K
- Compact, robust metal housing
- Excellent protection against short circuits
- Lightning protection and surge protection
- Redundant power supply: 48-57 V DC, redundant power supply with polarity reversal protection function
- Extended operating temperature range, -40 °C ~ +75 °C
- Removable terminal connection
- Number of ports: 4
- PoE Power budget: 30 W
- PoE standard: IEEE802.3at (PoE+)
- Ethernet speed: Gigabit
- Industrial usage: yes
- Installation type: DIN rail
- Managed: no
- Number of ports (Uplink): 2
- Outdoorsuitable: no
- PoE (Power over Ethernet): yes
- Protection against vandalism: no
- Uplink port connection: SFP
- VLAN: no

Package contents

- Industrial 4-port Gigabit PoE switch with 2 x SFP uplink
- Quick start guide

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	9.77	25.50	45.50	41.00	47,570.20
Packaging Unit Inside	1	0.98	18.60	23.10	8.40	3,609.14
Packaging Unit Single	1	0.98	18.60	23.10	8.40	3,609.14
Net single without Packaging	1	0.79	14.70	16.50	5.40	0.00

More images:

